

Standard configuration

Main body includes the warmer module, controller, bassinet, stand, I.V. Pole, tray.

Specification

- Power requirement: AC220V-230V/50HZ; 600W
- Mode of control: Pre-warm mode control, manual mode control and baby mode controlled by micro-computer
- Baby mode temperature control range: 34.5-37.5°C
- Temperature sensor display range: 5°C-65°C
- Accuracy of skin temperature sensor: $\leq 0.3^{\circ}\text{C}$
- Temperature uniformity of mattress: $\leq 2^{\circ}\text{C}$
- Angle of warmer module: 0° , 30° , 45° for two ways;
- Inclination of the bassinet: the five tile position;
- APGAR timer: it will give sound when the unit tones at 1' ,5' , 10' ;
- Failure alarm: over temperature alarm, deviation alarm, sensor failure alarm, power failure alarm, setting alarm, checking alarm and so on.

Environmental temperature

Operating range: 18 °C~30°C

Ambient air movement rate: $\leq 0.3\text{m/s}$

Package

Package: each unit is packed to one carton

Size: 111cm x 62.5cm x 119.5cm

Gross Weight: 60kg

NINGBO DAVID

HK N-90

INFANT RADIANT WARMER

NINGBO DAVID MEDICAL DEVICE CO.,LTD.

Sales Center:#100 Jinghua Rd, High-tech industrial development zone, Ningbo China

Tel:0086-574-87800008 87800009

Fax:0086-574-87803714

P.C.:315040

Http://www.nbdavid.com

E-mail:sales@chinadavid.cn

HKN-90 INFANT RADIANT WARMER



Brief introduction

- Three control modes: Pre-warm mode, manual mode and baby mode controlled by micro-computer;
- Set temperature and baby temperature can be displayed separately;
- Horizon angle of warmer module and inclination of the bassinet can be adjusted;
- The panels around bassinet can be disassembled;
- APGAR timer;
- Failure alarm indication;
- RS232 connector

Endless ve keeps the new life safe