

Pulse oximeter : IP-1010



Features

- Protection from motion artifact
- Accurate detection in low perfusion
- Compact & tabletop design
- Battery : 5 hours charging and 10 hours operating
- 130 hours trend memory
- Intuitive menu with 6 languages : English, French, German, Spanish, Italian, Portuguese
- Easy-to-see bright display
- Competitive price

It is specialized in detection of pure signals and has protection from motion artifact. It is designed for compact and light weight , which makes it possible to be versatile of hand-held and desktop. The screen display is capable to convert to plethysmograph as well as big-font mode . With the RS 232 computer interface , you can download and print out patient data to your network or PC.



Specifications

Measurement range
 SpO2 : 1 to 100%
 Pulse rate : 25 to 250 bpm
 Perfusion : 0.05 to 20 %

Saturation accuracy
 Saturation : 71 to 100%

	Without motion	With motion
Adults	±2 %	±3 %
Neonates	±3 %	±3 %
Low perfusion	±3 %	±3 %

Pulse rate accuracy
 Pulse rate : ±2 % 25 tp 250 bpm
 Without motion : ±3 %
 With motion: ± 5 %

Alarm limit
 SpO2: High range 100 %~ 26 % : Adjustment per 1 %
 Low range 25 %~99 %: Adjustment per 1 %
 Pulse rate: High range 250~26 BPM : Adjustment per 1 BPM
 Low range 25~249 BPM : Adjustment per 1 BPM

Power
 AC power requirements: 100 to 220 V, 50/60Hz
 Power consumption : 30 VA
 Battery Type: Li-Ion
 Charging time: 5 hours
 Operating time: 10 hours

Pulse oximeter with NIBP : IP-1020



Features

- 3 parameter vital sign monitor
- 72 hours trending and strong battery capacity
- Battery: 5 hours charging and 8 hours operating
- Automatic blood pressure mode : Min. 5 minutes to max. 8 hours interval
- Intuitive menu with 6 languages : English, French, German, Spanish, Italian, Portuguese
- Provides RS-232 and nurse call interface

It is designed for one of the most compact and light weight models in multi parameter devices. IP-1020 is combined with pulse oximeter and NIBP of three important functions in patient monitoring. This is unique and ideal combination and you will find it a maximum of efficiency at a minimum of cost.



Specifications

Measurement range
 SpO2 : 1 to 100 %
 Pulse rate : 25 to 250 bpm
 NIBP : Adult/Child

- Systolic : 50 to 255 mmHg
- Diastolic: 30 to 220 mmHg
- Mean : 40 to 235 mmHg
- Infant/Neonate
- Systolic : 30 to 130 mmHg
- Diastolic: 20 to 100 mmHg
- Mean : 25 to 120 mmHg

Accuracy
 Saturation : 71 to 100 %

	Without motion	With motion
Adults	±2 %	±3 %
Neonates	±3 %	±3 %
Low perfusion	±3 %	±3 %

Pulse rate : ±2 % 25 to 250 bpm
 Without motion : ±3 %
 With motion: ±5 %

NIBP
 Maximum standard deviation : ±8mmHg (1.1kPa)

Alarm limit
 SpO2: High range 100 %~ 26 % : Adjustment per 1 %
 Low range 25 %~99 %: Adjustment per 1 %
 Pulse rate: High range 250~26 BPM : Adjustment per 1 BPM
 Low range 25~249 BPM : Adjustment per 1 BPM
 NIBP : Systolic 260 mmHg~30 mmHg : Adjustment per 1 mmHg
 Diastolic 230 mmHg~20 mmHg: Adjustment per 1 mmHg
 Mean 240 mmHg~25mmHg: Adjustment per 1 mmHg

Power
 AC power requirements: 100 to 240 V, 50/60Hz
 Power consumption : 30 VA
 Battery Type: Li-Ion
 Charging time: 5 hours
 Operating time: 8 hours (With full load & NIBP auto mode 30 min.interval)

IP-1000 Series

Pulse oximeter and NIBP

CE 0470



Accessories

Section	P/N	Image	Description	Size	
SpO2 Probe	6108000		Adult Reusable Clip type Finger	2m	
	6108001		Child Reusable Clip type Finger	1m	
	6108002		Neonate Reusable Clip type Finger	1m	
	6108004		Adult/Child/Neonate Disposable Wrap Finger	1m	
Extension cable	6108003		Adult/Child/Neonate	2m	
Pole Clamp	13900004				
	NIBP Cuff	A7104000		Adult Reusable	24 x 32 cm
		A7104001		Big adult Reusable	31 x 40 cm
		A7104002		Child Reusable	18 x 20 cm
	A7104003		Pediatric Reusable	12 x 19 cm	
	A7104004		Infant Reusable	8 x 13 cm	

Distributor

Infunix
Technology

Infunix Technology Co., Ltd.

2F, Seokjin B/D, 46-12 Samseong-dong, Gangnam-gu, Seoul, South Korea, 135-863
 Tel: +82 2 3448 2800 / Fax: +82 2 546 8346
 Email: info@infunix.com URL: www.infunix.com

Ver 1.01090413