

D500


Defibrillator/Monitor



Saving Lives Everyday!

D500

Defibrillator/Monitor



LCD
ECG & Text display

colin NIBP

Temperature 1

Temperature 2

IBP 1

IBP 2

Respironics Capnography



Nellcor Oximax SpO2
Pulse Oximetry

Biphasic Defibrillation, Pacing and Complete Monitoring in one Portable Device.

- Multifunctional Defibrillator/Monitor
- Manual and AED Operation
- Non-invasive Pacing Mode
- Advanced Biphasic Technology
- Defibrillation with Paddles
- 12 Lead ECG Monitoring



Rechargeable Battery

Defibrillation Mode Selector

Manual / AED / Pacing / Monitor mode

Shock Button

Flashing button indicates ready for shock delivery.
Push the button to deliver shock.

Non-Invasive Pacing

SD card

Review data stored & software upgrade



12 Lead ECG Glasgow Algorithm

Paddle




D500 Defibrillator. Quality you can trust.

Monitoring-12 Lead ECG Display




Full range of monitoring options available, including 3/5/12 Lead ECG (Glasgow University), Mediana or Nellcor SpO2, Omron NIBP, IBP, Temp and Respiration EtCO2.

AED




Semi-Automatic AED mode with easy to follow step-by-step visual and audio instructions.

Manual Defibrillation




Biphasic Manual Defibrillation with maximum Energy level of 360 J. With Synchronous Cardioversion.

Non-Invasive Pacing




Demand and Non-Demand Pacing modes with Pacing rates adjustable from 30 to 180 ppm.

● **Biphasic Waveform**



Most effective Biphasic Truncated Exponential Waveform with impedance compensation. (25 to 175 Ohm)

● **Data Storage**



Powerful memory for saving of numerical data and ECG, EtCO2 and IBP waveforms. Saves data for up-to 100 patients and 250 events.

● **Dual Battery**



Dual Battery system with Automatic Switching. Each battery supports a minimum of 100 shocks and 5 hours operating time.

● **Integrated Thermal Printer**




Device features an integrated Printer with 80 mm Paper Width that can print up to 3 Channels and Report / Patient information.

● **Paddles**



● **Pads**



● **ECG Cables**



Display

Screen Size 170.0*128 (mm) (8.4 in diagonally across the TFT-LCD screen)
Screen Type/Color Liquid Crystal Display (LCD) Color
Resolution 800*600 pixel

Controls

Standard Knob; Mode key (Off, AED, Manual, Pacing); 12 soft buttons (Shock, Select Energy, Charge, Analyze, NIBP, REC, LEAD, Alarm Off, Size, Display, bpm, mA); 5 soft key

Alarms

Categories	Patient Status and System Status
Priorities	Low, Medium and High Priorities
Notification	Audible and Visual
Setting	Default and Individual
Alarm Volume Level	45 to 84 dB

Physical Characteristics and Printer

Instrument

Dimensions	348*256*332 (mm) (W*H*D) including a handle and paddles excluding options and accessories
Weight	Approx. 7.45 kg including paddles excluding optional configurations and accessories
Degree of Protection against Electric Shock	
ECG:	Type CF with defibrillation protection
Respiration:	Type CF with defibrillation protection
SpO2:	Type CF with defibrillation protection
Temperature:	Type CF with defibrillation protection
EtCO2	Type CF with defibrillation protection
Mode of Operation	Continuous

Printer

Type	Thermal
Weight	190g
Number of Channels	1 to 3 channels
Paper Width	80 mm
Printer Speed	25 mm/s

Electrical

Instrument

Power Requirement AC Mains 100 to 240 V, 50/60 Hz, 60 to 160 VA

Battery (Option)

Type	Li-ion battery
Voltage	10.8V / 7200mAh
Discharge	A minimum of 100 shocks at 200 Joules (per battery)
Operating Time	5 hours (per battery) At the following condition: no printing, no external communication, no audible alarm sound and room temperature: 25°C
Recharge	7 hours with D500 turned on/off
Dual Battery	Automatic Switching

Environmental Conditions

Operation

Temperature	0 to 40°C (32 to 104°F)
Humidity	15 to 95% RH, non-condensing
Altitude	-170 to 4,877 m (-557 to 16,000 ft)
Water Resistance	IP34

Transport and Storage (in shipping container)

Temperature	-20°C to 50°C (-4°F to 122°F)
Humidity	15 to 95% RH, non-condensing
Altitude	-304 to 6,096m (1,000 to 20,000ft)

Defibrillator

Biphasic Waveform	Biphasic Truncated Exponential
Resuscitation Guidelines	Selectable AHA/ERC

Manual Mode

Shock Energy Level	External Paddles: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 15, 20, 30, 40, 50, 75, 100, 150, 175, 200, 300, 360J
Automatic Discharge Time	60 seconds
Charging Time	Battery: 6 seconds (200J), 10 seconds (360J) AC power input: 10 seconds (200J), 15 seconds (360J)
Synchronous Cardioversion	Energy transfer begins within 60msec of the QRS peak

AED Mode

1 ch ECG measurement

Lead	Lead II
Patient Impedance	25 to 175 Ohm
Heart Rate	20 to 300 bpm

Delivered Energy

The D500 delivers shocks to load impedances from 25 to 175 Ohms. The duration of each pulse of the waveform is dynamically adjusted based on delivered charge, in order to compensate for patient impedance variation, as shown below;

Load resistance (Ohm)	Delivered energy (Joule)
25	195
50	190
75	185
100	195
125	190
150	185
175	180

Pacer

Pacing Mode	Demand or non-demand
Pacing rate	30 ppm to 180 ppm
Resolution	2 ppm
Accuracy	± 1.5 ppm
Output current	0 mA to 140 mA
Resolution	2 mA
Accuracy	± 5% or 5 mA
QRS Marker	in the demand mode

ECG

Heart Rate

Measurement Rate	0, 20 to 300 bpm
Resolution	1 bpm
Accuracy	±5 bpm

ECG (Electrocardiograph)

Leads	3 / 5 / 12 Lea Lead I, II, III, aVR, aVL, aVF, V1, V2, V3, V4, V5, V6, Paddles, Pads
Lead Off Detection	Detected and displayed
Pads Off Detection	Detected and displayed
Pacer Detection	Detected pacer pulses of ±2mV to ±700mV with pulse widths of 0.1 to 2msec and rise times 10% of width not to exceed 100msec

Input;

Input Impedance	5 M Ohm or more
Input Dynamic Range	±5mV AC, ±300mV DC
Voltage Range	±0.5mV ~ ±5mV
Signal Width	40 to 120 ms (Q to S)

Output (Frequency Response);

Monitoring mode	0.4 to 40 Hz
Diagnostic mode	0.05 to 150 Hz
Low-extended mode	0.05 to 40 Hz
Filter mode	1 to 21 Hz
ECG size	Auto, 5.0, 10.0, 15.0, 20.0, 30.0 mm/mV
Display Sweep Speeds	25.0 mm/sec
Display Sensitivity	10 mm/mV
Pacing Pulse Detection	On, Off
Electrode Disconnect Alarm	Display and/or sound
Common Mode Rejection (CMRR)	80 dB or more
Defibrillator Discharge Recovery	less than 5 sec per IEC 60601-2-27
Defibrillation Protection	Protected

Interpretive Algorithm

12-Lead Interpretive Algorithm University of Glasgow 12-Lead ECG Analysis Program

Respiration

IM Respiration

Technique Impedance Pneumography
Range 0,3 to 120 breaths/min
Resolution 1 breaths/min
Leads RA to LA
Base impedance 500 to 2000 ohm
Delta impedance 0.5 to 3 ohm
Lead Off Condition Detected and displayed
Defibrillator Protection Protected

AW Respiration

Technique Non-dispersive Infrared Spectroscopy
Range 0 to 120 breaths/min
Accuracy ± 1 breaths/min
Display Sweep Speeds 12.5 mm/sec

NIBP

Pulse Rate

Pulse Rate Range	Adult/Pediatric	40 to 200 bpm
	Neonatal	40 to 240 bpm

Resolution 5 bpm

NIBP (Non-Invasive Blood Pressure)

Technique Oscillometric Measurement

Measurement Modes Off, cont, 1, 2.5, 3, 5, 10, 15, 30, 60, 90 minutes

Measurement Range	Adult/Pediatric	SYS 60 to 250mmHg
		MAP 45 to 235mmHg
		DIA 40 to 200mmHg

Neonatal

SYS	40 to 120mmHg
MAP	30 to 100mmHg
DIA	20 to 90mmHg

NIBP Accuracy Mean error and standard deviation per ANSI/AAMI SP10:2002+A1:2003+A2:2006

Pressure Display Range	Adult/Pediatric	0 to 300 mmHg
	Neonatal	0 to 150 mmHg

Pressure Display Accuracy	Adult/Pediatric	± 10 mmHg
	Neonatal	± 5 mmHg

Initial Cuff Inflate Pressure	Adult/Pediatric	120, 140, 160, 180, 200, 220, 240, 260, 280mmHg
	Neonatal	80, 90, 100, 110, 120, 130, 140 mmHg

Automatic Cuff Protector	Adult/Pediatric:	300 mmHg
	Neonatal:	150 mmHg

Defibrillator Protection	Protected
Measurement Speed	About 20 seconds

IBP

Pulse Rate

Pulse Rate Range	20 to 250 bpm
Pulse Rate Resolution	1 bpm

IBP (Invasive Blood Pressure)

Parameter Displayed	P1, ABP P2, CVP, PAP, LAP
Measurement Range	-50 mmHg to 300 mmHg 20 bpm to 250 bpm

Resolution	1 mmHg
Input Sensitivity	5 μ V/V/mmHg
Transducer Volume Displacement	0.1 mm ³ /100 mmHg
Zero Calibration Range	± 100 mmHg
Frequency Response	25 Hz
Wave Size	0 to 20, 0 to 50, 0 to 100, 0 to 200, 0 to 300, Auto Size

Display Sweep Speeds	25.0 mm/s
Defibrillator Protection	Protected

SpO2

%Saturation

Range	0% to 100%
Perfusion Range	0.03% to 20 %
Accuracy Adults1	70% to 100% ± 2 digits
Neonate	70% to 100% ± 2 digits
Low Perfusion2	70% to 100% ± 2 digits
Display Sweep Speeds	12.5mm/sec, 25.0mm/sec & 50.0mm/sec
C-Lock	

Pulse Rate

Pulse Rate Range	25 to 240 bpm
Resolution	1 bpm
Accuracy	No motion: ± 3 bpm Motion: ± 5 bpm
Asystole Detection Time	± 8 sec
Delay	± 10 sec
Response Time	± 20 sec

- Adult specifications are shown for OXIMAX MAX-A and MAX-N sensors with the D500. Neonate specifications are shown for OXIMAX MAX-N sensors with the D500. Saturation accuracy will vary by sensor type.
- Specification applies to the D500 performance. Reading accuracy in the presence using signals supplied by a patient simulator. SpO2 and pulse rate values were varied across the monitoring range including weak signal conditions and compared to the known true saturation and pulse rate of the input signals.

Capnography

Display	EtCO ₂ , InCO ₂
Range	0 to 150 mmHg
Accuracy	0 to 40 mmHg ± 2 mmHg of reading 41 to 70 mmHg $\pm 5\%$ of reading 71 to 100 mmHg $\pm 8\%$ of reading 101 to 150 mmHg $\pm 10\%$ of reading
Display Accuracy	± 2 mmHg
Response Time	Mainstream: Less than 60ms Sidestream: Less than 3sec
Gas Compensation	User selective at O ₂ > 60% and N ₂ O > 50%
Warm Up time	2 minutes maximum
Sound Noise Level	Less than 41dB when ambient sound pressure level is 22dB
Sweep Speeds	6.25mm/sec, 12.5 mm/sec and 25.0 mm/sec

Temperature

Probe Types	Thermistor probe
Parameter displayed	TEMP1, TEMP2
Range	15°C to 45°C (59°F to 113°F)
Display Accuracy	$\pm 0.1^\circ\text{C}$ (25°C to 45°C) or $\pm 0.2^\circ\text{F}$ (77°F to 113°F) $\pm 0.2^\circ\text{C}$ (15°C to less than 25°C) Or $\pm 0.4^\circ\text{C}$ (59°F to less than 77°F)

Event

Date	12 lead, Events
Memory	Saves total 100 data (12 lead) Total 250 date (events) Saves date and time Saves alarm condition Saves HR/PR, NIBP, SpO ₂ , Temp, IBP1, IBP2, EtCO ₂ numeric data Saves ECG, EtCO ₂ , 2 channel IBP waveform data
Removable Memory	SD Card/USB

Optional Items

Non-invasive Blood Pressure with cuffs and cuff hoses
SpO₂ (Nellcor) with DS-100A and DOC-10
12 Lead ECG with Interpretation from the University of Glasgow
Continuous Temperature Monitoring
EtCO₂, selectable either Mainstream or Sidestream from Respironics
Invasive Blood Pressure Monitoring (2 lines)
Wi-Fi/3G Communication module
Wireless LAN data transmission
Additional Battery



Our mission is to save lives by developing, manufacturing and selling state-of-the-art medical technology.

Our ultimate goal is to earn the trust of our customers by using our imagination and skills to continuously offer better medical solutions.




Mediana Seoul Office

Mediana Building, #793-3, Bangbae-dong,
Seocho-ku, Seoul, Korea (P.C: 137-830)
Tel : +82-2-542-3375 Fax : +82-2-542-7447

Mediana Head Office / Factory / R&D

Wonju Medical Industry Park, #1650-1, Donghwa-ri,
Munmak-eup, Wonju-si, Gangwon-do, Korea (P.C : 220-801)
Tel : +82-33-742-5400 Fax : +82-33-742-5418

www.mediana.co.kr



The information contained in this document is subject to change without prior notice©